

### All-in-one LED Displays



AD	TL-110AD12A	700cd/m <sup>2</sup>	SMD	Pitch 1.27mm	24/7 Operation
	TL-137AD15A	700cd/m <sup>2</sup>	SMD	Pitch 1.58mm	24/7 Operation
	TL-165AD19A	700cd/m <sup>2</sup>	SMD	Pitch 1.90mm	24/7 Operation

### LED Video Wall



LV	Available from Q3 CY2026				
	TL-55LV12A	800cd/m <sup>2</sup>	COB	Pitch 1.26mm	24/7 Operation

### Wireless Presentation System

#### PressIT WPS2 Series



Note: The transmitter and receiver are also available separately.

Basic set		Transmitter	
TY-WPS2	TY-WPSC2	TY-WPB2	TY-WPBC2
1	1	2 X 1	3 X 1
2 X 2	3 X 2		
4	4		

### Professional Displays



Standard	NEW	EQ3
SQ3	TH-86SQ3	TH-86EQ3
4K	TH-75SQ3	TH-75EQ3
	TH-65SQ3	TH-65EQ3
	TH-55SQ3	TH-55EQ3
	TH-50SQ3	TH-50EQ3
	TH-43SQ3	TH-43EQ3

### 360 Degree Camera Speakerphone

#### PressIT360

#### TY-CSP1



#### Pict Descriptions

- 24/7 Operation: Capable of 24-hour continuous operation
- 18h Operation: Capable of 18-hour continuous operation
- Media Player: USB media player
- 4K Playback: Media File Playback
- Portrait: Portrait installation possible
- SMD LED type
- COB LED type
- Pitch 1.27mm: LED Pixel pitch

Pitch for wall hanging is VESA compliant. (Excluding All-in-one LED displays)

NOTE: The availability varies depending on model. The specifications are subject to change without notice.

For more information about Panasonic Professional Displays, please visit: Display Global Website.

