

● Product specification (design and specification subject to change without notice)

■ DISPLAY PANEL	
Aspect ratio	8:9
Power Requirements	DC 2.8 V/3.8 V
LED Type	3-in-1 COB
Pixel pitch	1.26 mm
Pixel count	16,200 pixels (H 120 x V 135)
■ MECHANICAL	
Dimension (W x H x D)	6.74" x 5.99" (171 x 152 mm)
Weight	Applox. 0.163 kg (0.4 lbs.)
Carton Dimensions (W x H x D)	9.53" x 1.97" x 8.59" (242 x 50 x 218 mm)
Gross Weight	Applox. 0.32 kg (0.8 lbs.)

● ENVIRONMENTAL

Operating Environment	Temperature : 0 °C to 40 °C (32 °F to 104 °F) ¹ : 0 °C to 35 °C (32 °F to 95 °F) ² Humidity : 20% to 80% (No condensation)
Operating Time	24 h / day ³

- 1 : for up to 4593 ft (1400 m) altitude
2 : for between 4593 ft (1400 m) and 9186 ft (2800 m) altitude
· Depending on the temperature or humidity conditions, uneven brightness may be observed. This is not a malfunction.
· This unevenness will disappear while applying current continuously. If not, consult the distributor.
3 : In case of running for a long time, the moving image is recommended to be displayed.

● DIMENSIONS

(Note) This drawing is not to scale.
Units: mm

