

List of Compatible Device Models

Logo Transfer Software

- As of July 2025 -

In using this software, bear in mind that the items whose settings must be selected for the projectors and the functions that can be used may differ from one projector model to another. While referring to the table below, check out that projector models are compatible with the software before using them.

List of models

PT-CMZ50	20	PT-DX500	14
PT-D10000	15	PT-DX610	13
PT-D12000	12	PT-DX800	13
PT-D4000	16	PT-DX810	13
PT-D5000	13	PT-DX820	9
PT-D5700	16	PT-DZ10K	9
PT-D6000	13	PT-DZ110XE	13
PT-DS100XE	13	PT-DZ12000	12
PT-DS12K	9	PT-DZ13K	9
PT-DS20K	9	PT-DZ16K	9
PT-DS20K2	9	PT-DZ16K2	9
PT-DS8500	13	PT-DZ21K	9
PT-DW100	12	PT-DZ21K2	9
PT-DW10000	15	PT-DZ570	14
PT-DW105XEA	13	PT-DZ6700	13
PT-DW11K	9	PT-DZ6710	13
PT-DW17K	9	PT-DZ680	13
PT-DW17K2	9	PT-DZ770	13
PT-DW5100	16	PT-DZ780	9
PT-DW530	14	PT-DZ870	9
PT-DW6300	13	PT-DZ8700	13
PT-DW640	13	PT-EW530	22
PT-DW730	13	PT-EW540	19
PT-DW740	13	PT-EW550	20
PT-DW750	9	PT-EW551	20
PT-DW830	9	PT-EW630	22
PT-DW8300	13	PT-EW640	19
PT-DW90XE	13	PT-EW650	20
PT-DX100	9	PT-EW651	20

(continued)

The software is not compatible with any device models that are not listed in “List of models”.

List of models

(continued)

PT-EW730	19	PT-LW25H	32
PT-EX12K	23	PT-LW336	17
PT-EX16K	23	PT-LW376	17
PT-EX500	22	PT-LX22	32
PT-EX510	19	PT-LX26	32
PT-EX520	20	PT-LX26H	32
PT-EX521	20	PT-LX30H	32
PT-EX600	22	PT-LZ370	31
PT-EX610	19	PT-MW530	9
PT-EX620	20	PT-MW630	9
PT-EX621	20	PT-MW730	9
PT-EX800	19	PT-MZ10K	9
PT-EZ57	20	PT-MZ11K	8
PT-EZ570	22	PT-MZ13K	9
PT-EZ580	19	PT-MZ14K	8
PT-EZ590	20	PT-MZ16K	9
PT-EZ591	20	PT-MZ17K	8
PT-EZ770	19	PT-MZ20K	8
PT-FRQ50	7	PT-MZ570	9
PT-FRQ60	7	PT-MZ670	9
PT-FRZ50	9	PT-MZ680	9
PT-FRZ55	9	PT-MZ682	9
PT-FRZ60	9	PT-MZ770	9
PT-FW430	29	PT-MZ780	9
PT-FW530	20	PT-MZ782	9
PT-FX400	29	PT-MZ880	9
PT-FX500	20	PT-MZ882	9
PT-FZ570	20	PT-RCQ10	8
PT-LB1	33	PT-RCQ80	8
PT-LB1V	33	PT-REQ10	8
PT-LB2	33	PT-REQ12	8
PT-LB2V	33	PT-REQ80	8
PT-LB3	33	PT-REZ10	8
PT-LB306	18	PT-REZ12	8
PT-LB356	17	PT-REZ80	8
PT-LB386	17	PT-RQ13K	9
PT-LB426	17	PT-RQ18K	6
PT-LB75V	34	PT-RQ22K	9
PT-LB78V	34	PT-RQ25K	6
PT-LB90	34	PT-RQ32K	9
PT-LB90NT	33	PT-RQ35K	6
PT-LMW420	20	PT-RQ35K2	6
PT-LMW460	20	PT-RQ50K	5
PT-LMX420	20	PT-RS11K	9
PT-LMX460	20	PT-RS20K	9
PT-LMZ420	20	PT-RS30K	9
PT-LMZ460	20	PT-RW330	11

(continued)

The software is not compatible with any device models that are not listed in "List of models".

List of models

(continued)

PT-RW430	11	PT-VMZ40	20
PT-RW620	9	PT-VMZ41	20
PT-RW630	9	PT-VMZ50	20
PT-RW730	9	PT-VMZ51	20
PT-RW930	9	PT-VMZ51S	20
PT-RX110	9	PT-VMZ60	20
PT-RZ120	9	PT-VMZ61	20
PT-RZ12K	9	PT-VMZ71	20
PT-RZ14K	6	PT-VW330	28
PT-RZ16K	9	PT-VW340	25
PT-RZ17K	6	PT-VW345N	25
PT-RZ21K	9	PT-VW350	25
PT-RZ24K	6	PT-VW355N	25
PT-RZ31K	9	PT-VW360	25
PT-RZ34K	6	PT-VW430	26
PT-RZ34K2	6	PT-VW431D	27
PT-RZ370	11	PT-VW435N	26
PT-RZ470	11	PT-VW440	26
PT-RZ475	11	PT-VW530	25
PT-RZ570	9	PT-VW535N	25
PT-RZ575	9	PT-VW540	24
PT-RZ660	9	PT-VW545N	24
PT-RZ670	9	PT-VX400	28
PT-RZ690	9	PT-VX400NT	28
PT-RZ770	9	PT-VX405	26
PT-RZ790	9	PT-VX406	25
PT-RZ870	9	PT-VX41	28
PT-RZ890	9	PT-VX410	25
PT-RZ970	9	PT-VX415N	25
PT-RZ990	9	PT-VX42	25
PT-ST10	33	PT-VX420	25
PT-SW280A	30	PT-VX421	25
PT-SX300A	30	PT-VX425N	25
PT-SX320A	30	PT-VX430	25
PT-TMW380	20	PT-VX45	26
PT-TMX380	20	PT-VX46	25
PT-TMZ400	20	PT-VX50	25
PT-TW230	32	PT-VX500	26
PT-TW231R	32	PT-VX501	26
PT-TW380	17	PT-VX505N	26
PT-TW381R	17	PT-VX51	24
PT-TX350	17	PT-VX510	26
PT-TX440	17	PT-VX60	25
PT-VMW50	20	PT-VX600	25
PT-VMW51	20	PT-VX605N	25
PT-VMW60	20	PT-VX61	24
PT-VMW61	20	PT-VX610	24

(continued)

The software is not compatible with any device models that are not listed in "List of models".

List of models

(continued)

PT-VX615N	24
PT-VZ470	25
PT-VZ570	25
PT-VZ575N	25
PT-VZ580	24
PT-VZ585N	24
TH-D10000	15
TH-DW10000	15

The software is not compatible with any device models that are not listed in "List of models".

PT-RQ50K

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/E/X/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	×	
	Communication rate (bps)	×	
	Parity	×	
	Projector ID	×	
Power state	Power on	×	
	Standby	○	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	—	
	On and during display of password input screen immediately after power on	—	
	On and following password input immediately after power on	—	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 2048 X 1080	
	Number of colors	Max. 16777216 colors (24-bit color)	When creating a new file (loading a bitmap), it is automatically converted to the correct number of colors.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	The following formats are not supported: Top-down, transparent data
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ PT-RQ35K2 / PT-RZ34K2 / PT-RQ35K / PT-RZ34K

■ PT-RQ25K / PT-RQ18K / PT-RZ24K / PT-RZ17K

■ PT-RZ14K

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/E/EJ/X/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	×	
	Communication rate (bps)	×	
	Parity	×	
	Projector ID	×	
Power state	Power on	×	
	Standby	○	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	—	
	On and during display of password input screen immediately after power on	—	
	On and following password input immediately after power on	—	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1920 X 1200	
	Number of colors	Max. 16777216 colors (24-bit color)	When creating a new file (loading a bitmap), it is automatically converted to the correct number of colors.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	The following formats are not supported: Top-down, transparent data
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

PT-FRQ60

PT-FRQ50

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/J/T/(blank), cabinet color: B/W)

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	×	
	Communication rate (bps)	×	
	Parity	×	
	Projector ID	×	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	—	
	On and during display of password input screen immediately after power on	—	
	On and following password input immediately after power on	—	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1920 X 1080	
	Number of colors	Max. 16777216 colors (24-bit color)	When creating a new file (loading a bitmap), it is automatically converted to the correct number of colors.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	The following formats are not supported: Top-down, transparent data
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ PT-REQ12 / PT-REQ10 / PT-REQ80

■ PT-REZ12 / PT-REZ10 / PT-REZ80

■ PT-RCQ10 / PT-RCQ80

■ PT-MZ20K / PT-MZ17K / PT-MZ14K / PT-MZ11K

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/E/EJ/J/UG/X/(blank), lens: L/(blank), cabinet color: B/W)

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	×	
	Communication rate (bps)	×	
	Parity	×	
	Projector ID	×	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	—	
	On and during display of password input screen immediately after power on	—	
	On and following password input immediately after power on	—	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1920 X 1200	
	Number of colors	Max. 16777216 colors (24-bit color)	When creating a new file (loading a bitmap), it is automatically converted to the correct number of colors.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	The following formats are not supported: Top-down, transparent data
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ PT-RQ32K / PT-RZ31K / PT-RS30K
 ■ PT-RQ13K
 ■ PT-RQ22K / PT-RZ21K / PT-RS20K
 ■ PT-RZ12K / PT-RS11K
 ■ PT-RZ16K
 ■ PT-RZ990 / PT-RZ890 / PT-RZ790 / PT-RZ690
 ■ PT-RZ120 / PT-RZ970 / PT-RW930 / PT-RX110 / PT-RZ870 / PT-RZ770 / PT-RW730 / PT-RZ660 / PT-RW620
 ■ PT-RZ670 / PT-RW630
 ■ PT-FRZ60 / PT-FRZ50 / PT-FRZ55
 ■ PT-RZ575 / PT-RZ570
 ■ PT-DZ21K2 / PT-DS20K2 / PT-DW17K2 / PT-DZ16K2
 ■ PT-DZ21K / PT-DS20K / PT-DW17K / PT-DZ16K
 ■ PT-DZ13K / PT-DS12K / PT-DW11K / PT-DZ10K
 ■ PT-DZ870 / PT-DW830 / PT-DX100
 ■ PT-DZ780 / PT-DW750 / PT-DX820
 ■ PT-MZ16K / PT-MZ13K / PT-MZ10K
 ■ PT-MZ882 / PT-MZ782 / PT-MZ682
 ■ PT-MZ880 / PT-MZ780 / PT-MZ680
 ■ PT-MZ770 / PT-MW730 / PT-MZ670 / PT-MW630 / PT-MZ570 / PT-MW530

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: A/D/E/J/T/U/X/(blank), lens: L/(blank), cabinet color: B/K/W/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1024 X 768	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

 PT-RZ475
 PT-RZ470 / PT-RW430
 PT-RZ370 / PT-RW330

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank), cabinet color: K/W/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	×	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

■ PT-DZ12000 / PT-D12000 / PT-DW100

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	○	
	Standby	○	Transfer operations using a LAN connection cannot be performed if network standby is OFF.
	During cooling	○	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	○	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 640 X 200	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	2	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

PT-DZ8700 / PT-DS8500 / PT-DW8300 / PT-DZ110XE / PT-DS100XE / PT-DW90XE / PT-DW105XEA
PT-DZ770 / PT-DW740 / PT-DX810
PT-DZ680 / PT-DW640 / PT-DX610
PT-DZ6710 / PT-DZ6700 / PT-DW6300 / PT-D6000 / PT-D5000
PT-DW730 / PT-DX800

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/U/(blank), lens: L/(blank), cabinet color: S/K/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	× ^{*1}	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: Only the PT-DZ110XE, PT-DS100XE, PT-DW90XE, PT-DW105XEA, PT-DZ770, PT-DW740 and PT-DX810 support LAN connection.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 640 X 200	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ PT-DZ570 / PT-DW530 / PT-DX500

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	ALL, 1 to 6 are generally available.
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1024 X 768	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ TH-DW10000 / TH-D10000 / PT-DW10000 / PT-D10000

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/U)

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	○	
	Standby	○	
	During cooling	○	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	○	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 640 X 200	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	2	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ PT-D5700 / PT-D4000 / PT-DW5100

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/U/(blank), lens: L/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 640 X 200	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ PT-LB426 / PT-LB386 / PT-LB356 / PT-LW376 / PT-LW336

■ PT-TW381R / PT-TW380 / PT-TX440 / PT-TX350

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/J/T/(blank))

[Communication and Transfer]

○: Possible X: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	ALL, 1 to 6	
Power state	Power on	X	
	Standby	○ (Standby mode: Normal)	
	During cooling	X	
	During power on process	X	
Security password setting	On and standby state	X	
	On and during display of password input screen immediately after power on	X	
	On and following password input immediately after power on	X	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible X: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	X	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	X	
Display position	Display at any position	X	

*1: Background color can be set only for the PT-LW376, PT-LW336, PT-TW381R and PT-TW380.

PT-LB306

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: (blank))

[Communication and Transfer]

○: Possible X: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	X	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	ALL, 1 to 6	
Power state	Power on	X	
	Standby	○ (Standby mode: Normal)	
	During cooling	X	
	During power on process	X	
Security password setting	On and standby state	X	
	On and during display of password input screen immediately after power on	X	
	On and following password input immediately after power on	X	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible X: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	X	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	X	
Display position	Display at any position	X	

■ PT-EZ770 / PT-EW730 / PT-EX800

■ PT-EZ580 / PT-EW640 / PT-EX610 / PT-EW540 / PT-EX510

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/J/Z/T/(blank), lens: L/(blank))

[Communication and Transfer]

○: Possible X: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	X*1	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	X	
	Standby	○ (Standby mode: Normal)	
	During cooling	X	
	During power on process	X	
Security password setting	On and standby state	X	
	On and during display of password input screen immediately after power on	X	
	On and following password input immediately after power on	X	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: Only the PT-EZ770, PT-EW730, and PT-EX800 support LAN connection.

[Logo Data]

○: Possible X: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1024 X 768	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ PT-EZ590 / PT-EW650 / PT-EW550 / PT-EX620 / PT-EX520 / PT-EZ57
 ■ PT-EZ591 / PT-EW651 / PT-EW551 / PT-EX621 / PT-EX521
 ■ PT-FZ570 / PT-FW530 / PT-FX500
 ■ PT-VMZ71 / PT-VMZ61 / PT-VMZ51 / PT-VMZ51S / PT-VMZ41 / PT-VMW61 / PT-VMW51
 ■ PT-CMZ50
 ■ PT-LMZ460 / PT-LMZ420 / PT-LMW460 / PT-LMW420 / PT-LMX460 / PT-LMX420 / PT-TMZ400 / PT-TMW380 / PT-TMX380
 ■ PT-VMZ60 / PT-VMZ50 / PT-VMZ40 / PT-VMW60 / PT-VMW50

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: A/D/J/K/T/(blank), lens: L/(blank), cabinet color: B/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-EZ590, PT-EW650, PT-EW550, PT-EZ57, PT-EZ591, PT-EW651, PT-EW551, PT-FZ570, PT-FW530, PT-VMZ71, PT-VMZ61, PT-VMZ51, PT-VMZ51S, PT-VMZ41, PT-VMW61, PT-VMW51, PT-LMZ460, PT-LMZ420, PT-LMW460, PT-LMW420, PT-TMZ400, PT-TMW380, PT-VMZ60, PT-VMZ50, PT-VMZ40, PT-VMW60 and PT-VMW50.

■ PT-EZ570 / PT-EW630 / PT-EX600 / PT-EW530 / PT-EX500

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/EP/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal, Network)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-EZ570, PT-EW630 and PT-EW530.

PT-EX16K
PT-EX12K

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	×	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

■ PT-VZ585N / PT-VW545N / PT-VX615N

■ PT-VZ580 / PT-VW540 / PT-VX610 / PT-VX61 / PT-VX51

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/J/K/K1/T/(blank))

[Communication and Transfer]

○: Possible X: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	ALL, 1 to 6	
Power state	Power on	X	
	Standby	○ (Standby mode: Normal)	
	During cooling	X	
	During power on process	X	
Security password setting	On and standby state	X	
	On and during display of password input screen immediately after power on	X	
	On and following password input immediately after power on	X	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible X: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1024 X 768	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

PT-VZ575N / PT-VW535N / PT-VX605N
PT-VZ570 / PT-VW530 / PT-VX600 / PT-VX406 / PT-VX46 / PT-VX60 / PT-VX50
PT-VZ470
PT-VW360 / PT-VX430
PT-VW355N / PT-VX425N
PT-VW350 / PT-VX420 / PT-VX421
PT-VW345N / PT-VX415N
PT-VW340 / PT-VX410 / PT-VX42

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/EA/J/T/Z/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	× ^{*1}	
	Serial connection	○	
	Communication rate (bps)	9600 ^{*2}	
	Parity	NONE ^{*2}	
	Projector ID	ALL, 1 to 6	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: Only the PT-VX406, PT-VX46, PT-VW360 and PT-VX430 support LAN connection.

*2: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○ ^{*1}	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-VZ575N, PT-VW535N, PT-VZ570, PT-VW530, PT-VZ470, PT-VW360, PT-VW355N, PT-VW350, PT-VW345N and PT-VW340.

■ PT-VW440 / PT-VX510

■ PT-VW435N / PT-VX505N / PT-VW430 / PT-VX501 / PT-VX500 / PT-VX405 / PT-VX45

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/EP/KEA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	× ^{*1}	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE ^{*2}	
	Projector ID	— ^{*2}	
Power state	Power on	×	
	Standby	○ (Standby mode: Network)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: Only the PT-VX405 and PT-VX45 support LAN connection.

*2: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○ ^{*1}	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-VW440, PT-VW435N and PT-VW430.

PT-VW431D

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Network)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

PT-VW330 / PT-VX400NT / PT-VX400 PT-VX41

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/EP/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Network)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-VW330.

PT-FW430 / PT-FX400

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	ALL, 1 to 6	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

PT-SW280A / PT-SX320A / PT-SX300A

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	ALL, 1 to 6	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-SW280A.

PT-LZ370

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	ALL, 1 to 6	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

PT-LW25H / PT-LX30H / PT-LX26H / PT-LX26 / PT-LX22 **PT-TW231R / PT-TW230**

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Network)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-LW25H, PT-TW231R and PT-TW230.

PT-LB90NT

PT-LB3 / PT-LB2V / PT-LB2 / PT-LB1V / PT-LB1 / PT-ST10

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible X: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	X	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	X	
	Standby	○ (Standby mode: Normal)	
	During cooling	X	
	During power on process	X	
Security password setting	On and standby state	X	
	On and during display of password input screen immediately after power on	X	
	On and following password input immediately after power on	X	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible X: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	—	
	Security screen	—	
Screen effect	Transparent color specification	X	
	Background color specification	X	
Enlarge	Display enlargement function on projector side	X	
Display position	Display at any position	X	

PT-LB90 / PT-LB78V / PT-LB75V

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	—	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	×	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	